



## DIMENSIONAL TABLES

WELDED TUBES  
SEAMLESS TUBES

OD up to 230 mm and w.t. up to 12.5 mm

OD up to 380 mm and w.t. up to 25 mm.

ID		OD	WT	Mass
Nominal	H8 Tolerance (mm)	(mm)	(mm)	(Kg/m)
<b>20</b>	- 0 / + 0.033	25	2.5	1.39
		30	5	3.08
		32	6	3.85
		35	7.5	6.33
		40	10	7.30
<b>25</b>	- 0 / + 0.033	35	5	3.70
		40	7.5	6.01
		45	10	8.60
<b>30</b>	- 0 / + 0.033	38	4	3.35
		40	5	4.32
		45	7.5	6.93
		50	10	9.86
<b>32</b>	- 0 / + 0.039	45	6.5	6.17
		42	5	4.56
<b>35</b>	- 0 / + 0.039	45	5	4.93
		50	7.5	7.86
		55	10	11.10
<b>40</b>	- 0 / + 0.039	50	5	5.67
		52	6	6.93
		55	7.5	8.79
		60	10	12.33
<b>45</b>	- 0 / + 0.039	55	5	6.30
		57	6	7.55
		60	7.5	9.85
		65	10	13.70

\* Tolerance H9

\*\* Tolerance H10.