

## DIMENSIONAL TABLES

ID		OD	WT	Mass
Nominal	H8 Tolerance (mm)	(mm)	(mm)	(Kg/m)
<b>110</b>	- 0 / + 0.054	120*	5	14.70
		125	7.5	22.30
		130	10	30.20
		135	12.5	37.76
		140	15	46.30
<b>115</b>	- 0 / + 0.054	125*	5	14.80
		130	7.5	22.66
		135	10	30.83
		140	12.5	39.30
<b>120</b>	- 0 / + 0.063	130*	5	16.00
		135	7.5	24.20
		140	10	32.70
		145	12.5	40.84
		150	15	50.00
<b>125</b>	- 0 / + 0.063	135*	5	19.40
		140	7.5	25.20
		145	10	34.00
		150	12.5	43.10
		155	15	51.80
<b>130</b>	- 0 / + 0.063	140*	5	17.30
		145	7.5	26.20
		150	10	35.30
		155	12.5	43.93
		160	15	53.70
<b>135</b>	- 0 / + 0.063	150	7.5	26.36
		155	10	35.76
		160	12.5	45.47

\* Tolerance H9

\*\* Tolerance H10.



ID		OD	WT	Mass
Nominal	H8 Tolerance (mm)	(mm)	(mm)	(Kg/m)
<b>140</b>	- 0 / + 0.063	150*	5	18.80
		155	7.5	28.10
		160	10	37.50
		165	12.5	48.00
		170	15	57.40
<b>145</b>	- 0 / + 0.063	160**	7.5	28.21
		165	10	38.22
<b>150</b>	- 0 / + 0.063	160**	5	20.20
		165	7.5	30.10
		170	10	40.50
		175	12.5	50.09
		180	15	61.10
<b>155</b>	- 0 / + 0.063	165**	5	19.73
		170	7.5	30.06
		175	10	40.69
		180	12.5	51.63
<b>160</b>	- 0 / + 0.063	170**	5	20.35
		175	7.5	30.98
		180	10	43.10
		185	12.5	54.30
		190	15	64.80
		195	17.5	76.60
		200	20	88.78
<b>165</b>	- 0 / + 0.063	175**	5	20.96
		180	7.5	31.91
		185	10	43.16
		195	15	66.58
		200	17.5	78.76

\* Tolerance H9

\*\* Tolerance H10.