

## DIMENSIONAL TABLES

ID		OD	WT	Mass
Nominal	H8 Tolerance (mm)	(mm)	(mm)	(Kg/m)
<b>170</b>	- 0 / + 0.063	180**	5	21.58
		185	7.5	32.83
		190	10	44.39
		195	12.5	52.26
		200	15	68.43
<b>175</b>	- 0 / + 0.063	190	7.5	33.75
		195	10	45.62
		200	12.5	57.80
		205	15	70.28
<b>180</b>	- 0 / + 0.072	200	10	48.30
		205	12.5	59.40
		210	15	72.20
		215	17.5	85.23
		220	20	98.64
<b>185</b>	- 0 / + 0.072	200	7.5	35.60
		205	10	59.39
		215	15	73.98
		220	17.5	87.39
<b>190</b>	- 0 / + 0.072	210	10	49.32
		215	12.5	62.42
		220	15	75.83
<b>195</b>	- 0 / + 0.072	210	12.5	60.88
		220	12.5	63.96
		225	15	77.68
		230	17.5	91.71

\* Tolerance H9

\*\* Tolerance H10.



ID		OD	WT	Mass
Nominal	H8 Tolerance (mm)	(mm)	(mm)	(Kg/m)
<b>200</b>	- 0 / + 0.072	210**	5	25.28
		215	7.5	30.92
		220	10	51.81
		225	12.5	65.60
		235	17.5	93.90
<b>210</b>	- 0 / + 0.072	230	10	54.25
		240	15	83.23
		245	17.5	98.18
<b>220</b>	- 0 / + 0.072	245	12.5	71.67
		250	15	86.93
<b>225</b>	- 0 / + 0.072	245	10	57.95
<b>250</b>	- 0 / + 0.081	280	15	98.03

\* Tolerance H9

\*\* Tolerance H10.

Note: the present table reports only the most common sizes; on request it is possible to supply other sizes and tolerances as well.