

## DIMENSIONAL TABLES

ID (mm)	WT (mm)	Tolerance on the ID (mm)	OD		Mass (Kg/m)	
			Nominal (mm)	Tolerance (mm)		
<b>63</b>	2.5	- 0 / + 0.120	68	± 0.30	4.00	
	3		69		4.89	
	3.5		70		5.74	
	4	- 0 / + 0.074	71	± 0.35	6.61	
	5		73		8.39	
	6		75		10.21	
<b>65</b>	2.5	- 0 / + 0.120	70	± 0.30	4.10	
	3		71		± 0.35	5.04
	3.5		72			5.92
	4	73	6.81			
	5	- 0 / + 0.074	75	± 0.35	8.00	
	7.5		80		14.33	
<b>70</b>	2.5	- 0 / + 0.120	75	± 0.35	4.40	
	3		76		5.41	
	3.5		77		6.35	
	4		78		7.30	
	5	- 0 / + 0.074	80	± 0.40	9.20	
	6		82		11.25	
	7.5		85		14.33	
<b>75</b>	2.5	- 0 / + 0.120	80	± 0.35	4.78	
	3		81		5.78	
	3.5		82		6.78	
	4	- 0 / + 0.074	83	± 0.40	7.80	
	5		85		9.80	
	7.5		90		15.26	
<b>80</b>	2.5	- 0 / + 0.120	85	± 0.40	5.09	
	3		86		6.10	
	3.5		87		7.21	
	4		88		8.29	
	5	- 0 / + 0.074	90	± 0.45	10.48	
	6		92		12.73	
	7.5		95		16.18	
<b>85</b>	3.5	- 0 / + 0.140	92	± 0.45	7.64	
	4	- 0 / + 0.140	93		8.72	
	5	- 0 / + 0.087	95		11.10	



ID (mm)	WT (mm)	Tolerance on the ID (mm)	OD		Mass (Kg/m)
			Nominal (mm)	Tolerance (mm)	
<b>90</b>	3	- 0 / + 0.140	96	± 0.45	6.89
	3.5		97		8.08
	4		98		9.28
	5	- 0 / + 0.087	100	± 0.50	11.70
	6		102		14.20
	7.5		105		18.03
<b>95</b>	3	- 0 / + 0.140	101	± 0.50	7.26
	3.5		102		8.51
	4		103		9.77
	5	- 0 / + 0.087	105	± 0.50	12.34
	7.5		110		18.96
<b>100</b>	3	- 0 / + 0.140	106	± 0.50	7.60
	3.5		107		8.94
	4		108		10.26
	5	- 0 / + 0.087	110	± 0.50	12.95
	7.5		115		19.88
<b>110</b>	3.5	- 0 / + 0.140	117	± 0.50	9.80
	4		118		11.25
	5	- 0 / + 0.087	120	± 0.70	14.19
	7.5		125		21.73
<b>120</b>	3.5	- 0 / + 0.140	127	± 0.70	10.66
	4		128		12.24
	5	- 0 / + 0.087	130	± 0.70	15.42
	7.5		135		23.58
<b>125</b>	3.5	- 0 / + 0.160	132	± 0.70	11.00
	4		133		12.73
	5	- 0 / + 0.100	135	± 0.70	16.03
	7.5		140		24.51