

## DIMENSIONI E TOLLERANZE

Diametro interno finito mm	Tolleranza Diametro interno mm	Diametro esterno mm	Spessore del grezzo mm	Peso del grezzo Kg/m
----------------------------	--------------------------------	---------------------	------------------------	----------------------

<b>230</b>	-0/+0,072	<b>254</b>	16,0	93,9
	-0/+0,072	<b>267</b>	25,0	150,0
	-0/+0,072	<b>273</b>	25,0	154,0
	-0/+0,072	<b>298,5</b>	40,0	255,0
	-0/+0,072	<b>323,9</b>	50,0	338,0

<b>235</b>	-0/+0,072	<b>254</b>	12,5	74,4
	-0/+0,072	<b>273</b>	22,2	137,0

<b>240</b>	-0/+0,072	<b>267</b>	17,5	107,0
	-0/+0,072	<b>273</b>	20,0	125,0
	-0/+0,072	<b>298,5</b>	35,0	227,0
	-0/+0,072	<b>305</b>	40,0	261,0

<b>250</b>	-0/+0,072	<b>267</b>	12,5	79,0
	-0/+0,072	<b>273</b>	14,2	90,9
	-0/+0,072	<b>298,5</b>	30,0	198,0
	-0/+0,072	<b>305</b>	35,0	232,0
	-0/+0,072	<b>323,9</b>	40,0	280,0
	-0/+0,072	<b>330</b>	45,0	316,0
	-0/+0,072	<b>343</b>	60,0	418,0

<b>254</b>	-0/+0,081	<b>267</b>	12,5	79,0
	-0/+0,081	<b>273</b>	14,2	90,9

<b>260</b>	-0/+0,081	<b>298,5</b>	25,0	170,0
	-0/+0,081	<b>323,9</b>	40,0	280,0
	-0/+0,081	<b>330</b>	40,0	285,0
	-0/+0,081	<b>343</b>	50,0	361,0

<b>270</b>	-0/+0,081	<b>298,5</b>	16,0	111,0
	-0/+0,081	<b>305</b>	22,2	154,0
	-0/+0,081	<b>323,9</b>	35,0	249,0
	-0/+0,081	<b>355,6</b>	50,0	377,0

Diametro interno finito mm	Tolleranza Diametro interno mm	Diametro esterno mm	Spessore del grezzo mm	Peso del grezzo Kg/m
----------------------------	--------------------------------	---------------------	------------------------	----------------------

<b>280</b>	-0/+0,081	<b>298,5</b>	12,5	88,8
	-0/+0,081	<b>305</b>	16,0	113,0
	-0/+0,081	<b>323,9</b>	25,0	186,0
	-0/+0,081	<b>330</b>	30,0	221,0
	-0/+0,081	<b>343</b>	35,0	265,0
	-0/+0,081	<b>355,6</b>	45,0	349,0
	-0/+0,081	<b>368</b>	50,0	391,0
	-0/+0,081	<b>406,4</b>	80,0	644,0

<b>290</b>	-0/+0,081	<b>323,9</b>	22,2	165,0
	-0/+0,081	<b>343</b>	30,0	231,0
	-0/+0,081	<b>355,6</b>	40,0	311,0
	-0/+0,081	<b>368</b>	45,0	358,0

<b>300</b>	-0/+0,081	<b>323,9</b>	16,0	121,0
	-0/+0,081	<b>330</b>	20,0	152,0
	-0/+0,081	<b>343</b>	25,0	195,0
	-0/+0,081	<b>355,6</b>	35,0	276,0
	-0/+0,081	<b>368</b>	40,0	323,0
	-0/+0,081	<b>381</b>	45,0	372,0
	-0/+0,081	<b>406,4</b>	60,0	513,0

<b>305</b>	-0/+0,081	<b>323,9</b>	14,2	109,0
	-0/+0,081	<b>343</b>	25,0	195,0
	-0/+0,081	<b>355,6</b>	30,0	241,0

<b>320</b>	-0/+0,089	<b>343</b>	16,0	128,0
	-0/+0,089	<b>355,6</b>	22,2	183,0
	-0/+0,089	<b>368</b>	30,0	249,0
	-0/+0,089	<b>381</b>	35,0	298,0
	-0/+0,089	<b>406,4</b>	50,0	439,0
	-0/+0,089	<b>419</b>	60,0	531,0



## DIMENSIONI E TOLLERANZE

Diametro interno finito mm	Tolleranza Diametro interno mm	Diametro esterno mm	Spessore del grezzo mm	Peso del grezzo Kg/m
----------------------------	--------------------------------	---------------------	------------------------	----------------------

<b>330</b>	-0/+0,089	<b>355,6</b>	16,0	33,0
	-0/+0,089	<b>381</b>	30,0	259,0
	-0/+0,089	<b>394</b>	40,0	349,0

<b>340</b>	-0/+0,089	<b>394</b>	35,0	309,0
	-0/+0,089	<b>406,4</b>	40,0	361,0
	-0/+0,089	<b>419</b>	45,0	421,0

<b>350</b>	-0/+0,089	<b>368</b>	12,5	109,0
	-0/+0,089	<b>394</b>	30,0	269,0
	-0/+0,089	<b>406,4</b>	35,0	320,0
	-0/+0,089	<b>419</b>	40,0	373,0
	-0/+0,089	<b>457,2</b>	60,0	587,0
	-0/+0,089	<b>445</b>	55,0	528,0

<b>360</b>	-0/+0,089	<b>406,4</b>	30,0	278,0
	-0/+0,089	<b>419</b>	35,0	331,0
	-0/+0,089	<b>445</b>	50,0	486,0
	-0/+0,089	<b>457,2</b>	60,0	587,0
	-0/+0,089	<b>470</b>	60,0	606,0

<b>370</b>	-0/+0,089	<b>419</b>	30,0	288,0
	-0/+0,089	<b>457,2</b>	50,0	502,0

<b>380</b>	-0/+0,089	<b>406,4</b>	16,0	153,0
	-0/+0,089	<b>419</b>	25,0	245,0
	-0/+0,089	<b>457,2</b>	45,0	464,0
	-0/+0,089	<b>508</b>	70,0	756,0

<b>400</b>	-0/+0,089	<b>419</b>	14,2	142,0
	-0/+0,089	<b>445</b>	30,0	306,0
	-0/+0,089	<b>457,2</b>	35,0	364,0
	-0/+0,089	<b>470</b>	40,0	423,0
	-0/+0,089	<b>508</b>	60,0	663,0

Diametro interno finito mm	Tolleranza Diametro interno mm	Diametro esterno mm	Spessore del grezzo mm	Peso del grezzo Kg/m
----------------------------	--------------------------------	---------------------	------------------------	----------------------

<b>420</b>	-0/+0,097	<b>457,2</b>	25,0	266,0
	-0/+0,097	<b>508</b>	50,0	565,0
	-0/+0,097	<b>558,8</b>	85,0	993,0

<b>430</b>	-0/+0,097	<b>508</b>	45,0	521,0
------------	-----------	------------	------	-------

<b>450</b>	-0/+0,097	<b>470</b>	16,0	179,0
	-0/+0,097	<b>508</b>	35,0	408,0
	-0/+0,097	<b>521</b>	40,0	474,0
	-0/+0,097	<b>558,8</b>	60,0	738,0

<b>500</b>	-0/+0,097	<b>530</b>	20,0	252,0
	-0/+0,097	<b>558,8</b>	35,0	451,0
	-0/+0,097	<b>609,6</b>	60,0	814,0

<b>600</b>	-0/+0,110	<b>660,4</b>	40,0	612,0
------------	-----------	--------------	------	-------

N.B.: Nella presente tabella vengono riportate solo le dimensioni più usuali; su specifica richiesta è possibile fornire dimensioni o tolleranze diverse da quelle indicate.