


# TABELLA DIMENSIONALE



Dimensione esterna lati <b>b</b> mm	Spessore <b>s</b> mm	Massa lineare Kg/m	Area della sezione metallica <b>A</b> cm <sup>2</sup>	Momento d'inerzia di flessione <b>I</b> cm <sup>4</sup>	Raggio d'inerzia <b>i</b> cm	Modulo di resistenza <b>W</b> cm <sup>3</sup>	Momento d'inerzia di torsione <b>J</b> cm <sup>4</sup>	Modulo di torsione <b>C</b> cm <sup>3</sup>
<b>40</b>	<b>2,0</b>	2,31	2,94	6,94	1,54	3,47	11,28	5,23
	<b>3,0</b>	3,30	4,21	9,32	1,49	4,66	15,80	7,07
	<b>4,0</b>	4,20	5,35	11,07	1,44	5,54	19,44	8,48
	<b>5,0</b>	4,99	6,36	12,30	1,39	6,13	22,30	9,48
<b>50</b>	<b>3,0</b>	4,25	5,41	19,47	1,90	7,79	32,13	11,76
	<b>4,0</b>	5,45	6,95	23,74	1,85	9,49	40,42	14,43
	<b>5,0</b>	6,56	8,36	27,04	1,80	10,82	47,46	16,56
	<b>6,0</b>	7,56	9,63	29,50	1,75	11,80	53,20	18,20
	<b>6,3</b>	7,57	9,65	27,90	1,70	11,20	53,00	18,00
<b>60</b>	<b>3,0</b>	5,19	6,61	35,13	2,31	11,71	57,09	17,65
	<b>4,0</b>	6,71	8,55	43,55	2,26	14,52	72,64	21,97
	<b>5,0</b>	8,13	10,36	50,49	2,21	16,83	86,42	25,61
	<b>6,0</b>	9,45	12,00	56,10	2,16	18,70	98,40	28,60
	<b>6,3</b>	9,55	12,20	54,40	2,11	18,10	100,00	28,80
<b>70</b>	<b>3,0</b>	6,13	7,81	57,50	2,71	16,40	92,40	24,70
	<b>4,0</b>	7,97	10,15	72,12	2,67	20,61	118,52	31,11
	<b>5,0</b>	9,70	12,36	84,63	2,62	24,18	142,21	36,65
	<b>6,0</b>	11,30	14,40	95,20	2,57	27,20	163,00	41,40
	<b>6,3</b>	11,53	14,69	93,77	2,53	26,79	168,14	42,10
	<b>7,1</b>	12,66	16,13	99,33	2,48	28,38	181,61	44,95
	<b>8,0</b>	13,85	17,64	104,11	2,43	29,74	194,36	47,56
<b>80</b>	<b>3,0</b>	7,07	9,01	87,80	3,12	22,00	140,00	33,00
	<b>4,0</b>	9,22	11,75	111,04	3,07	27,76	180,44	41,84
	<b>5,0</b>	11,27	14,36	131,44	3,03	32,86	217,83	49,68
	<b>6,0</b>	13,20	16,80	149,00	2,98	37,30	252,00	56,60
	<b>6,3</b>	13,51	17,21	148,51	2,94	37,13	260,96	57,90
	<b>7,1</b>	14,89	18,97	158,81	2,89	39,70	284,12	62,33
	<b>8,0</b>	16,36	20,84	168,38	2,84	42,09	307,14	66,61
	<b>10,0</b>	19,28	24,56	182,50	2,73	45,62	346,25	73,51
<b>90</b>	<b>3,0</b>	8,01	10,20	127,00	3,53	28,30	201,00	42,50
	<b>4,0</b>	10,48	13,35	161,92	3,48	35,98	260,80	54,17
	<b>5,0</b>	12,84	16,36	192,93	3,43	42,87	316,26	64,70
	<b>6,0</b>	15,10	19,20	220,00	3,39	49,00	368,00	74,20
	<b>6,3</b>	15,49	19,73	221,13	3,35	49,14	382,33	76,21
	<b>7,1</b>	17,12	21,81	238,13	3,30	52,92	418,55	82,53
	<b>8,0</b>	18,87	24,04	254,59	3,25	56,58	455,59	88,83
	<b>10,0</b>	22,42	28,56	281,64	3,14	62,59	523,18	99,83