



TABELLE DIMENSIONALI

TUBI SALDATI

Diametri fino a 230 mm e spessori fino a 12.5 mm

TUBI SENZA SALDATURA

Diametri fino a 380 mm e spessori fino a 25 mm

| Diametro interno | | Diametro esterno | Spessore | Peso |
|------------------|----------------------------------|------------------|----------|--------|
| Nominale | Tolleranza Ammessa H8 (mm) | (mm) | (mm) | (Kg/m) |
| 20 | - 0 / + 0.033 | 25 | 2.5 | 1.39 |
| | | 30 | 5 | 3.08 |
| | | 32 | 6 | 3.85 |
| | | 35 | 7.5 | 6.33 |
| | | 40 | 10 | 7.30 |
| 25 | - 0 / + 0.033 | 35 | 5 | 3.70 |
| | | 40 | 7.5 | 6.01 |
| | | 45 | 10 | 8.60 |
| 30 | - 0 / + 0.033 | 38 | 4 | 3.35 |
| | | 40 | 5 | 4.32 |
| | | 45 | 7.5 | 6.93 |
| | | 50 | 10 | 9.86 |
| 32 | - 0 / + 0.039 | 45 | 6.5 | 6.17 |
| | | 42 | 5 | 4.56 |
| 35 | - 0 / + 0.039 | 45 | 5 | 4.93 |
| | | 50 | 7.5 | 7.86 |
| | | 55 | 10 | 11.10 |
| 40 | - 0 / + 0.039 | 50 | 5 | 5.67 |
| | | 52 | 6 | 6.93 |
| | | 55 | 7.5 | 8.79 |
| | | 60 | 10 | 12.33 |
| 45 | - 0 / + 0.039 | 55 | 5 | 6.30 |
| | | 57 | 6 | 7.55 |
| | | 60 | 7.5 | 9.85 |
| | | 65 | 10 | 13.70 |

* Tolleranza ammessa H9

** Tolleranza ammessa H10.