

TABELLE DIMENSIONALI

Diametro interno		Diametro esterno	Spessore	Peso
Nominale	Tolleranza Ammessa H8 (mm)	(mm)	(mm)	(Kg/m)
50	- 0 / + 0.039	60	5	6.94
		62	6	8.46
		65	7.5	10.80
		70	10	15.00
		75	12.5	19.26
55	- 0 / + 0.046	55	5	7.58
		70	7.5	11.80
		75	10	16.20
60	- 0 / + 0.046	70	5	8.22
		72	6	9.97
		75	7.5	12.70
		80	10	17.50
		90	15	27.74
63	- 0 / + 0.046	73	5	8.38
		75	6	10.30
		77	7	12.08
		78	7.5	13.10
		83	10	18.00
65	- 0 / + 0.046	75	5	8.85
		80	7.5	13.60
		85	10	18.50
70	- 0 / + 0.046	80	5	9.48
		82	6	11.50
		85	7.5	14.60
		90	10	20.00
		100	15	31.44
75	- 0 / + 0.046	85	5	10.10
		90	7.5	15.60
		95	10	21.30

* Tolleranza ammessa H9

** Tolleranza ammessa H10.



Diametro interno		Diametro esterno	Spessore	Peso
Nominale	Tolleranza Ammissa H8 (mm)	(mm)	(mm)	(Kg/m)
80	- 0 / + 0.046	90	5	10.80
		92	6	13.00
		95	7.5	16.50
		100	10	22.50
		105	12.5	28.90
		110	15	35.20
85	- 0 / + 0.054	95	5	11.40
		100	7.5	17.50
		105	10	23.80
		110	12.5	30.50
		115	15	37.00
90	- 0 / + 0.054	100	5	12.10
		102	6	14.60
		105	7.5	18.40
		110	10	25.00
		115	12.5	31.60
		120	15	38.84
95	- 0 / + 0.054	105	5	12.33
		110	7.5	18.96
		115	10	25.89
		120	12.5	33.14
100	- 0 / + 0.054	110	5	13.40
		112	6	15.68
		115	7.5	20.30
		120	10	27.60
		125	12.5	35.20
105	- 0 / + 0.054	115	5	13.56
		120	7.5	20.81
		125	10	28.36
		130	12.5	36.22

* Tolleranza ammissa H9

** Tolleranza ammissa H10.